



DIESEL GENERATOR SET

50 Hz

SERVICE

Power	kVA
Power	kW
Speed	r.p.m
Standart Voltage	V
Power Factor	Cos Phi

STAND BY

275

1500

400/230

0,8

PRIME

250

200

Prime Power (PRP)

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2005, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.



+90 532 65 35 pbx
info@ideaglb.com

IDEA GLOBAL TRADING

Kucukbakkalköy Mah. Kırmızı Sunbul Sk. Gonul Sitesi

A Blok D:7 34750 Ataşehir / İstanbul

+90 532 375 65 35 | www.ideaglb.com

ENGINE

SPECIFICATIONS

Manufacturer		DOOSAN
Model		P126TI-II
Cylinder Configuration		INLINE
No of Cylinders		6
Displacement		11,1 lt
Bore		123 mm
Stroke		155 mm
Compression Ratio		17:01
Aspiration Type		TURBOCHARGE-INTERCOOLER
Governor Type		ELECTRONIC
Cooling System		WATER
Coolant Capacity	lt	51 lt
Lubrication Oil Capacity	lt	23 lt
Electrical System (DC)		24 VDC
Speed/ Frequency	rpmz	1500 rpm / 50 Hz rpm
Engine Gross Power	kW	294 kW
Fuel Consumption %110 ESP	lt	56,8 lt/h
Fuel Consumption %100 ESP	lt	51,9 lt/h
Fuel Consumption %75 ESP	lt	38,7 lt/h
Fuel Consumption %50 ESP	lt	25,7 lt/h
Exhaust Outlet Temperature	°C	590 °C
Exhaust Gas Flow	m3/min	47,4 m3/min
Combustion Air Flow	m3/min	20,1 m3/min
Cooling Air Flow	m3/min	295 m3/min

ALTERNATOR

SPECIFICATIONS

Number Of Phases		3
Power Factor		0,8
No of Bearings		Single
No of Poles		4
No of Leads		6-12
Insulation Class		H
Degree of Protection		IP23
Excitation System		AVR

OPTIONAL GENSET CONTROLLERS

Next generation single gen-set controllers for Stand-by and Prime power applications combining multi-functionality and wide communication with EFI engines.

Datakom SMART 200



Datakom D500



Datakom D500-GSM



EMKO Trans-AUTO



DEEPSEA 7320



ComAp AMF25



	Datakom SMART 200	Datakom D500	Datakom D500-GSM	Deepsea 6120	Deepsea 7320	ComAp AMF25	EMKO Trans-AUTO
Automatic Mains Monitoring	✓	✓	✓	✓	✓	✓	✓
Manuel Start	✓	✓	✓	✓	✓	✓	✓
Remote Start	OPTIONAL	OPTIONAL	✓	X	OPTIONAL	OPTIONAL	OPTIONAL
Remote Monitoring With Sim Card	X	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
1 Additional Option (Horn, Oil-Fuel Heater Etc.)	✓	✓	✓	✓	✓	✓	✓
Light Warning And Mimic Diagram	✓	✓	✓	✓	✓	✓	✓
Battery Charger	✓	✓	✓	✓	✓	✓	✓
Rs-485 Communication	OPTIONAL	✓	✓	X	✓	OPTIONAL	✓
Ethernet (Tcp-Ip) Communication	X	✓	✓	X	OPTIONAL	OPTIONAL	OPTIONAL

GENSET CONTROLLERS FOR SYNCHRONIZATION SYSTEMS

Next generation synchronizing genset controller capable of every communication and functionality.

Datakom D500 MK2



Datakom D700



DEEPSEA 8610




DEEPSEA 8620



DEEPSEA 8660



ComAp IntelliCompact NT SPTM




ComAp IntelliGen BaseBox



ComAp IntelliGen 200




DIMENSIONS



OPEN TYPE

WxLxH	mm	1300 x 3000 x 1700
Weight	kg	2120
Fuel Tank Capacity	lt	385



CANOPIED

WxLxH	mm	1300 x 3940 x 1850
Weight	kg	2685
Fuel Tank Capacity	lt	385

SOUND PROF CANOPIED

- Special design for minimizing acoustic level
- Galvanized steel construction further protected by polyester powder coat paint
- Black finish stainless steel locks and hinges
- Control panel viewing window in a lockable access door
- Emergency stop push button (red) mounted on enclosure exterior
- Lifting, drag and jacking points on base frame
- Radiator fill via removable, flush mounted rain cap fitted with compression seal

OPTIONAL EQUIPMENTS

Some of our Optional Equipments which can be provided with Generator Sets But not limited to;

- Medium voltage alternator
- Remote radiator applications
- External fuel tanks. Automatic and Manuel fuel filling system from external fuel tanks
- Fuel tank heater, oil pan heater, Anti-condensation heater
- Alternator with PMG (Permanent Magnet Generator)
- Synchronization systems
- Double Walled Fuel Tanks
- Container type canopy
- Lube oil and fuel drain pumps
- Trailer
- Remote monitoring options on the control panel